



Specification of Digital Components CDP/DAC/DVD

MODEL	TYPE	DAC TYPE RESOLUT.	OUTPUT IMPEDANCE (ohm)	DISTORS. % THD S/N RATIO	DIGITAL IN / OUT	FREQUENCY RESPONSE	ANALOG OUTPUTS	TYPE OF POWER SUPPLY	SPEC ' S DATA
ALPHA-24	CD-PLAYER FRONT LOADING	192 KHZ 24 BIT DSP O-S	15 OHM 2.3 VOLT	0.1% 90 db	OPTIONAL OUT: -SPDF -AES/EBU -OPTO TOSLINK ST-II	20 - 20 KHz	PAIR RCA OPTIONAL: BALANCED XLR	INTERNALY	400 (L) x 85 (H) x 300 (D) KG.6 NET 50-60 HZ 50 VA 110/230 V-AC
ALPHATOP 24	CD-PLAYER TOP LOADING	192 KHZ 24 BIT	15 OHM 2.3 VOLT	0.1% 90 db	OPTIONAL OUT: -SPDF -AES/EBU -OPTO TOSLINK ST-II	20-20 KHz	PAIR RCA OPTIONAL: BALANCED XLR "A"	INTERNALY	400 (L) x 100 (H) x 300 (D) KG.10 NET 110/230 VAC 50/60HZ 70VA
DIGIDRIVE T.L. with PSU - DTL	TOP-LOADING REFERENCE CD-TRANSPORT	NONE ONLY DIG-OUT	SPDF: 75 OHM AES-EBU: 110 OHM	NOT APPLICABLE	OPTIONAL OUT: -OPTO TOSLINK -OPTO S T -II	NOT APPLICABLE	NOT AVAILABLE	EXTERNAL BY PSU-DTL	400 (L) x 100 (H) x 300 (D) KG.10 NET PSU-DTL:225x85x300 110/230 VAC 50/60HZ 70VA
DIGICODE 2.20 with PSU - 220	TUBE ANALOG DIGITAL to ANALOG CONVERTER	DUAL MONO 20 BIT HI- RESOLUTION	150 OHM 2.4 VOLT	0.1% 93 db	IN:SPDF/AES-EBU OPTIONAL IN: -OPTO TOSLINK -OPTO ST-II	20-20 KHz	PAIR RCA OPTIONAL: BALANCED XLR "A"	EXTERNAL BY PSU-218	400 (L) x 108 (H) x 300 (D) KG.12 NET PSU-218:225x85x300 110/230 VAC 50/60HZ 80VA
DF-119.2	CD-PLAYER TRANSPORT FRONT LOADING	ONLY DIGITAL OUT SPDF/AES-EBU	SPDF: 75 OHM AES-EBU: 110 OHM	NOT APPLICABLE	OPTIONAL: -TOSLINK -OPTO ST-II	NOT APPLICABLE	NOT AVAILABLE	INTERNALY	400 (L) x 100 (H) x 300 (D) KG. 7 NET 50/60 HZ 50 V/A 110/230 V-AC
DA-1n	DIGITAL-ANALOG CONVERTOR	96 KHZ 24 BIT	15 OHM 2.5 VOLT	0.01 % 95 db	IN:SPDF/AES-EBU OPTIONAL: -TOSLINK -OPTO ST-II	20-20 KHz	PAIR RCA OPTIONAL: BALANCED	INTERNALY	400(L)x85(H)x300(D) KG.6 NET 50 V/A 110/230 VAC 50/60 HZ

ALL UNITS MEET CE-EMC-LVD REGULATION